

Prolong Acme Screw Assembly Reliability and Life

Proper lubrication is the key to continued performance and reliability of acme screw assemblies.

Use E-100 spray and PAG-1 grease lubricants to maximize life of your acme screw assembly.

LUBRICATION FOR PRECISION LEAD SCREW ASSEMBLIES



PAG-1 and E-100 LUBRICANT BENEFITS

- Shear Stability
- High Temperature Resistant
- Corrosion Protection
- Separation Resistant
- Extreme Pressure Properties
- Shelf Stable
- Water Resistant

PAG-1 and E-100 SPECIFICATIONS		
NLGI GRADE NUMBER	2	
PENETRATION (worked)	285	
DROPPING POINT	550°F	
GELLING AGENT	Synthetic	
OIL VISCOSITY	cst @ 40°C	96
	cst @ 100°C	11.3
TEMPERATURE RANGE	15°F TO 400°F	

PAG-1 GREASE

1 lb. Can or One-time use packets.

PAG-1 GREASE	
PART NAME	PAG-1
NET CONTENTS PER UNIT	1 lb.
PART # NLU-1001	1 CAN weight of 1 lbs.
PART # NLU-2001	1 CASE with 12 cans total weight of 13 lbs.
PART NAME	PAG-45
NET CONTENTS PER UNIT	.45 oz.
PART # NLU-2000	1 CASE with 50 packets weight of 1 lb. 6.5.oz.

E-100 SPRAY 12 oz. Spray Can

E-100 SPRAY CAN	
PART NAME	E-100
NET CONTENTS PER UNIT	12 oz.
PART # NLU-1002	1 CAN weight of 1 lb.
PART # NLU-2002	1 CASE with 12 cans total weight of 15 lbs.